



Padura StandLicht Re-400

Freestanding lighting with no rigging.

Padura StandLicht Re-400 – Professional Lighting Without Rigging.

Maximum light quality with zero overhead rigging: the StandLicht Re-400 combines two high-output Re-400 LED Fresnel fixtures in a freestanding system extending up to 4 m. Ideal for trade shows, events, and road-shows—mobile, efficient, and ready to run straight out of the case.

Technical Specifications

Supply voltage:	190 – 264 V AC, 47 – 63 Hz
Light source:	2 x Padura® 400 W + 400 W COB-Chip
Color rendering index (CRI):	Ra >96
Control:	DMX512:1990 or stand-alone 100 K
Power consumption:	max. 550 W
Beam angle:	ca. 18° – 58° (variable optics / zoom)
DMX in/out:	Neutrik® XLR 5-Po
IP rating:	IP20
Protection class:	I (protective earth)
Weight:	ca. 8 kg
Mains input:	Neutrik® PowerCON True1
Safety certificate:	Yes
Operating temperature:	0 – 40 ° C



Padura Elektronik GmbH
Ludwig-Erhard-Str. 17
33397 Rietberg
Tel.: +49 (0) 5244 90 369 20
info@padura-elektronik.de
www.padura-elektronik.de

Distribution partner:
LUCCS Light Systems GmbH
Allee 16, 33161 Hövelhof
Tel.: +49 (0) 5257 99 4810
info@lucss.lighting
www.lucss.lighting